



Variable temperature range -15°C and -25°C	Friendly-digital temperature displays
Efficient and environmentally-friendly refrigerants	White coated sheet steel housing
Forced-air cooling or static configuration	Interior light

Structural specifications

Internal and external structure data	
External material	white
Door material	steel
Internal material	commercial grade moulded
Controller data	
Temperature display	external digital
Key lock data	
Key lock	Options
Refrigerant gas data	
Type of refrigerant	R 600a FC free
Alarm security data	
Alarm type	Visual and audible high temperature

Model code variations

Interior volume	Temperature	Drawers	Cooling system	Description	Model code
70		2	Static	70 liters, white external material and static configuration	G70
100		4	Static	100 liters, white external material and static configuration	G100
		3	Ventilated	100 liters, white external material and ventilated configuration	G100V
150		5	Static	150 liters, white external material and static configuration	G150
		5	Ventilated	150 liters, white external material and ventilated configuration	G150V
220		6	Static	220 liters, white external material and static configuration	G220
	-15...-25°C	5	Ventilated	220 liters, white external material and ventilated configuration	G220V
280		6	Ventilated	280 liters, white external material and ventilated configuration	G280V
		7	Static	320 liters, white external material and static configuration	G320
320		7	Ventilated	320 liters, white external material and ventilated configuration	G320V
		8	Static	360 liters, white external material and static configuration	G360
360		8	Ventilated	360 liters, white external material and ventilated configuration	G360V
		8	Static	400 liters, white external material and static configuration	G400
400		8	Ventilated	400 liters, white external material and ventilated configuration	G400V

Technical specifications

Model	G70	G100 G100V	G150 G150V	G220 G220V	G280V	G320 G320V	G360 G360V	G400 G400V
Temperature data								
Temperature range [°C]	-15...-25	-15...-25	-15...-25	-15...-25	-15...-25	-15...-25	-15...-25	-15...-25
Measures								
Net capacity [liters]	68	100	150	200	253	300	350	399
External dimensions [WxDxH mm]	553x524x631	553x624x851	600x632x1250	600x632x1447	600x630x1644	600x630x1841	697x750x1751	697x750x1947
Controller data								
Type of control	electronic	electronic	electronic	electronic	electronic	electronic	electronic	electronic
Cooling data								
Cooling system	Static	Static or forced air	Static or forced air	Static or forced air	Forced air	Static or forced air	Static or forced air	Static
Illumination data								
Interior light	light	light	light	light	light	light	light	light
Shelf grid data								
Drawers	2	3	5	5/6	6	7	8	8
Alarm data								
Warning alarm	Visual and audible	Visual and audible	Visual and audible	Visual and audible	Visual and audible	Visual and audible	Visual and audible	Visual and audible
Sound power data								
Sound power level [dB]	39	40	41	41	39	40	40	40
Electrical data								
Rated Voltage [V]	220/240	220/240	220/240	220/240	220/240	220/240	220/240	220/240
Power Frequency [Hz]	50	50	50	50	50	50	50	50